


AIR6N0-C-MB NX 4×USB3.2-A

YUAN
Visualize Intelligent Planet

Card Size AI Edge with Multi AIoT Expansion

Features

- Powered by NVIDIA Jetson Orin™ NX up to 100 / 70 TOPS
- Business Card Size
- 2×M.2, Gen 4×2 M Key / Gen 4×1 E Key
- 1×USB3.2 Gen2, 4×USB3.2 Gen1
- 1×Mini DisplayPort





Specifications

System	
CPU	NVIDIA Jetson Orin™ NX 8GB 6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3
GPU	1024-Core NVIDIA Ampere Architecture GPU with 32 Tensor Cores
AU Performance	NVIDIA Jetson Orin™ NX 8GB 70 TOPS
System Memory	NVIDIA Jetson Orin™ NX 8GB 8GB LPDDR5
Interface	
Storage	Supports External NVMe 1×Micro SD Card Slot
Display Interface	1×Mini DP1.4
Ethernet	1×RJ45 for 10/100/1000Mbps Ethernet DHCP Client
Expansion Slot	1×M.2 2230 M Key PCIe Gen4×2 Slot 1×M.2 2230 E Key PCIe Gen4×1 Slot
USB	1×USB3.2 Gen2 (Type-C) 4×USB3.2 Gen1 (Type-A)
MIPI	2×4MIPI CSI-2 Lanes (D-PHY 2.1, Support MIPI Camera, Capture Card)
Peripheral Communication	10 Pin Header 1×USB2.0 4×GPIO 1×I2C
	6 Pin Wafer 1×UART(*)
	2×6 Pin Header 3×GPIO 1×RS485 1×I2C
	8 Pin Phoenix Connector 1×RS232(*) 1×I2C 1×GPIO
Misc. Features	* Please select either 1×UART or 1×RS232 to use Firmware Upgradable

SDK/Software


Video Feature	
Video Encode	AV1 (UHP) 1×4K60 3×4K30 6×1080p60 12×1080p30
	H.265 (UHP) 1×4K60 3×4K30 6×1080p60 12×1080p30
	H.264 (UHP) 1×4K60 2×4K30 5×1080p60 11×1080p30
Video Decode	AV1 (Main Profile) 1×8K30 2×4K60 4×4K30 9×1080p60 20×1080p30
	H.265 (Main, Main10) 1×8K30 2×4K60 4×4K30 9×1080p60 18×1080p30
	H.264 (Baseline, Main, High) 1×4K60 2×4K30 5×1080p60 11×1080p30
VP9 (Profile 0, Profile 2) 1×4K60 3×4K30 7×1080p60 15×1080p30	
SDK	
QCAP	Capture High Performance Renderer Image Snapshot Deinterlace, Alpha Blending Engine Auto Signal Detection 2D/3D Video, Audio and VANC Streams Capture
	Record Encrypt / Sync / Clone / Recording Time-Shifting / Rewind / Pre-Event / Recording Multi-Streams (3D) Recording Animation Transition Effect Video Cropping, Scaling and Alpha Blending Engine
	Stream 2D/3D Universal Stream Client 2D/3D Multi-Streams Stream Server RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*), Dante AV-H (*) Animation Transition Effect Video Cropping, Scaling and Alpha Blending Engine *Separate License Required
QDEEP	AI SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications Face Recognition Objects Detection Objects Segment Optical Character Recognition License Plate Recognition Customizable Video AI Functions Upon Request
Software (Optional)	
Xtremer	Web Based User Interface
	Encode / Decode AV1, H.26X
	Color Format Adjust 444 / 422 / 420, 10Bit / 8Bit Select
SCP	Record MP4, TS
	Stream / Network RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*) Dante AV-H (*) *Separate License Required
	Stream Multi-Streams Stream Server RTSP, RTMP, HLS, SRT, TS, WebRTC, Full NDI (*), NDI-HX(*), Dante AV-H(*) *: Separate License Required



Environment

Development Environment	
OS	Ubuntu: 20.04
Kernel	5.10.104-tegra or Higher
BSP	Linux for Tegra(L4T) R35.3.1 or Higher
SDK	JetPack 5.1.1 or Higher
Environment	
Power Supply	DC input : 9~24V
Power Consumption	TBA
Operating Temperature	Standard Version: 0~60 ° C with Airflow
Storage Temperature	-20~80 ° C


Mechanical



- Dimension of main Board: 90mm×55mm
- Weight: 175g (Including SOM, Fan and Daughter Board)



IO Layout

- Carrier Board



1. Battery
2. FAN
3. Recovery
4. Power
5. MIPI
6. Mini DisplayPort1.4
7. DC Pin Header (19V)
8. RJ45
9. USB3.2 Gen 2 Type-C
10. M.2 2230 M Key (PCIe Gen4×2)
11. M.2 2230 E Key (PCIe Gen4×1)
12. 80 Pin Header (Connect with Daughter Board)
13. 6 Pin Wafer
14. 10 Pin Header

• Daughter Board



- 15. USB3.2 (Gen 1) Type A
- 16. USB3.2 (Gen 1) Type A
- 17. USB3.2 (Gen 1) Type A
- 18. USB3.2 (Gen 1) Type A
- 19. 2x6 Pin Header
- 20. Micro SD Card Slot
- 21. 8 Pin Phoenix Connector
- 22. 80 Pin Header (Connect with Carrier Board)

* All registered trademarks are the property of their owners. The photo is for reference only.

* Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.

Licensees or representatives such as MPEG4, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.

