EYE6N0-S678

Al video Smart City Camera

Features

- 4K60 HDR/WDR smart camera with video AI processing capability powered by NVIDIA Jetson Orin NX Super
- Up to 157 TOPS AI performance, supports multiple AI models and Generative AI
- Hardware ISP design without CPU/GPU Loading
- Lens support auto-focus and auto-IRIS
- DMA PCIe design high-bandwidth capture, providing RGB444 image quality
- IP66 waterproof rating withstand outdoor tolerance within temperature from -20~50°C

Camera Specifications

Sensor Specifications				
Max Resolution	3840x2160 (8M)	Frame Rate	60	
Shutter	Rolling Shutter	Sensor Size	1/1.8"	
Pixel Size	2.0 x 2.0 μm	Sensor Model	CMOS	
Color/Mono	Color	Lens	Build in Focal lens	
Min illumination / light sensitivity (Color)	TBD	Min illumination / light sensitivity (B/W)	TBD	
Lens Specifications				
Focal Length	10.2mm (W) ~ 29.5mm (T)	Aperture	F1.6 (W) ~ F1.7 (T)	
FOV(D)	52~16.6 degree	Mount	Build in	
IRIS Control	DC Auto IRIS	IR Cut Filter	Can be switched on or off	
Video Tuning Specifications				
Shutter Speed	1/30(1/25) second – 1/76800 second	Auto Gain Control	60dB	
HDR	Yes (2 Frames)	WDR	Yes	
2D/3DNR	Yes	Low Light Gain Technology	Yes	
Video Adjustment	Brightness, contrast, hue, saturation, sharpness, horizontal flip, vertical flip, rotation, overexposure suppression	EV Value	EV - 2 ~ EV + 2	

System Specifications

System			
СРИ	NVIDIA Jetson Orin™ NX 8GB Super 6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3	NVIDIA Jetson Orin™ NX 16GB Super 8-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 2MB L2 + 4MB L3	
GPU	1024-Core NVIDIA Ampere Architecture GPU with 32 Tensor Cores		
AI Performance	NVIDIA Jetson Orin™ NX 8GB Super 117 TOPS	NVIDIA Jetson Orin™ NX 16GB Super 157 TOPS	
System Memory	NVIDIA Jetson Orin™ NX 8GB Super 8GB LPDDR5	NVIDIA Jetson Orin™ NX 16GB Super 16GB LPDDR5	
Interface			
Storage	Supports External NVMe		
Display Interface	1xHDMI2.0		
Ethernet	1×RJ45 for 10/100/1000Mbps Ethernet DHCP Client		
Wireless	Wi-Fi 6		
Expansion Slot (M.2)	M.2 1×M.2 2280/3080 M Key PCIe Gen4×4 Slot 1×M.2 2230 M Key PCIe Gen4×2 Slot 1×M.2 2230 E Key PCIe Gen4×1 Slot		
USB	1×USB3.2 Gen2 (Type-C)		







Key Points

Wireless Network	
Wi-Fi Support	Wi-Fi 802.11 a/b/g/n/ac/ax
Mobility Network	
Mobility Module	5G / 4G / 3G SIM Module
5G Support	Sub-6 SA Non-SA
4G Support	LTE Cat20 LTE FDD LTE TDD
3G Support	HSPA+

SDK / Software

Video Feature	
Video Encode	AV1 (UHP) 1×4K60 H.265 (UHP) 1×4K60 H.264 (UHP)
SDK	1×4K60
QCAP	Capture High Performance Renderer Image Snapshot Deinterlace, Alpha Blending Engine Auto Signal Detection 2D/3D Video, Audio and VANC Streams Capture
	Record Encrypt / Sync / Clone / Recording Time-Shifting / Rewind / Pre-Event / Recording Multi-Streams (3D) Recording Animation Transition Effect Video Cropping, Scaling and Alpha Blending Engine
	Stream 2D/3D Universal Stream Client 2D/3D Multi-Streams Stream Server RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*), Dante AV-H (*) Animation Transition Effect Video Cropping, Scaling and Alpha Blending Engine *Separate License Required
QDEEP	Al SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications Face Recognition Objects Detection Objects Segment Optical Character Recognition License Plate Recognition Customizable Video Al Functions Upon Request
Software (Optional)	
Xtreamer	Web Based User Interface Encode / Decode AV1, H.26X Color Format Adjust 444 / 422 / 420, 10Bit / 8Bit Select Record MP4, TS Stream / Network RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*), Dante AV-H (*)

Environment

Development Environment	
JetPack	6.2 or Higher
System Spec	
Power Supply	DC Input : TBA
Power Consumption	ТВА
Operating Temperature	-20~50 °C
IP Rating	IP66

Mechanical

- Dimension of Case: 10cm(W)x10cm(H)x23cm(D)
- Weight: TBA

 - * All registered trademarks are the property of their owners. The photo is for reference only. * Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.



Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.